



## **MK-770EXP™ FEATURES**

- Powerful high torque universal motor
- Built-in fully adjustable miter system for precise 45° angle cuts
- A single adjustment point permits the orientation of the blade to an exact 45° angle in seconds
- Variable height cutting head allows for plunge cutting and use of blades smaller than 7" in diameter
- Chrome guide-bar and linear-bearing assembly ensures precise alignment and precision cutting
- Zinc-plated steel frame and cast aluminum components
- Hinged blade guard for easy blade changes and maintenance inspection
- New zinc-plated splash cover protects motor from water mist
- 7" wet cutting continuous rim blade & submersible water pump included
- CSA approved
- One-year limited warranty

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

[www.mkdiamond.com](http://www.mkdiamond.com) | [customerservice@mkdiamond.com](mailto:customerservice@mkdiamond.com)



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



## **MK-770EXP™ 1-1/4 HP, 7" Wet Cutting Tile Saw**

The MK-770EXP Tile Saw uses a powerful 1-1/4 HP motor which delivers high torque and consistent RPM during all cutting operations. The MK-770EXP is built with a unitized steel frame. It features a pivoting cutting head for precision 45° miter cuts. One-year limited warranty.

<b>Motor</b>	Electric
<b>Power</b>	1-1/4 HP, 120V
<b>Blade Capacity</b>	7" (178 mm)
<b>Depth of Cut</b>	2" (51 mm)
<b>Depth of Cut at 45°</b>	1-1/8" (32 mm)
<b>Length of Cut</b>	20" (508 mm)
<b>Diagonally Cut</b>	14" (356 mm) Tile
<b>L x W x H (inches)</b>	37" x 22" x 23"
<b>L x W x H (mm)</b>	940 x 559 x 584
<b>Weight</b>	57 lbs. (26 kg)
<b>Includes</b>	<ul style="list-style-type: none"> <li>• 7" Wet Cutting Diamond Blade</li> <li>• Water Pump</li> <li>• Rip Guide</li> </ul>
<b>Part#</b>	160267

<b>Optional</b>	Stand	Stand w/ Casters
<b>Part#</b>	151889	160197



Hinged blade guard for easy blade changes and maintenance inspection



Built-in fully adjustable miter system easily orients the cutting head assembly from 0° to 45° in seconds



Chrome plated guide-bar and linear-bearing assembly ensure precise alignment and precision cutting